NUCLEATION SITE ACTIVATION

IN

SATURATED BOILING

NUCLEATION SITE ACTIVATION
IN SATURATED BOILING

by

MAMDOUH S. M. SHOUKRI, B.Sc. (Eng.)

A Thesis

Submitted to the School of Graduate Studies
in Partial Fulfilment of the Requirements
for the Degree

Master of Engineering

McMaster University

March 1974

TO SUSAN

TITLE: Nucleation Site Activation in Saturated Boiling

AUTHOR: MAHMOUD SHOUKRI MAHMOUD SHOUKRI,
B.Sc. (Mech. Eng.),
(Cairo University, Cairo, Egypt)

SUPERVISOR: Dr. Ross L. Judd

NUMBER OF PAGES: ix, 115

SCOPE AND CONTENTS:

An experimental investigation is presented for boiling of distilled water at atmospheric pressure on a copper surface having three different surface finishes of 16, 5 and 4 μ inch CLA. Activation of the nucleation cavities under three different levels of heat flux for each surface was investigated. The measured active cavity radii showed good agreement with the active site radii as predicted by both the Hsu and Han and Griffith models. As a result of this investigation it was apparent that small cavities were able to entrap vapour residue and be activated by their neighbours and that the reason for incipience delay as reported in the literature was due to the nonexistence of sufficiently large cavities with the prerequisite residue of gas or vapour.

The correlation suggested by Brown relating $(N/A)_{r_c}$ as a function of r_c in the form $(N/A)_{r_c} \propto (1/r_c)^m$ was confirmed. On the basis of this work, it is recommended that the parameter group $[2\sigma T_s / \rho_v h_{fg} (T_w - T_s)]$ be used to characterize a boiling surface.

ACKNOWLEDGEMENTS

It is my pleasure to express my sincere gratitude to Dr. Ross L. Judd for his expert guidance, valuable advice and continuous encouragement throughout the duration of the present investigation.

The author also expresses his appreciation to Ms. BettyAnne Bedell for typing the manuscript.

The financial support provided by the National Research Council through grant A4362 is also acknowledged.

TABLE OF CONTENTS

	Page
CHAPTER 1 INTRODUCTION	1
CHAPTER 2 LITERATURE SURVEY	3
CHAPTER 3 EXPERIMENTAL APPARATUS	14
3.1 Design Criteria	14
3.2 Test Assembly	14
3.3 Nucleation Site Locating System	16
3.4 Photographic System	17
3.5 Regulatory System	20
3.6 Temperature Measuring System	21
3.7 Power and Control	23
CHAPTER 4 TEST CONDITIONS	27
CHAPTER 5 TEST PROCEDURE	31
CHAPTER 6 RESULTS	35
CHAPTER 7 ANALYSIS AND DISCUSSION	43
CHAPTER 8 CONCLUSIONS	77
APPENDIX A ANALYSIS OF THE UNIDIRECTIONALITY OF HEAT FLOW	79
APPENDIX B INTERFEROMETRY	88
APPENDIX C DETERMINATION OF SURFACE TEMPERATURE UNCERTAINTY	92
APPENDIX D UNCERTAINTY ANALYSIS	98
APPENDIX E EXPERIMENTAL DATA	101
APPENDIX F PROPERTIES OF THE COPPER SPECIMEN	110
NOMENCLATURE	111
REFERENCES	113

LIST OF FIGURES

FIGURE

PAGE

1	Effect of Surface Roughness on the Boiling of Water	4
2	Surface Roughness vs Surface Superheat at Constant h	6
3	Superheat Layer Thickness Correlation	13
4	Sectional View of Test Assembly	15
5	Nucleation Site Locating System	18
6	Photographic System	19
7	Thermocouple Locations	22
8	Thermocouple Assembly	22
9	Thermocouple Circuit	24
10	Power Circuit Diagram	25
11	Experimental Arrangements	26
12	Talysurf Profiles of the Three Surfaces	28
13	Boiling Characteristic Curves	36
14	Nucleation Site Density vs Surface Superheat	37
15	Nucleation Site Density vs Heat Flux	38
16	Distribution of the Cavity Radius of the 16 μ inch CLA Surface	40
17	Distribution of the Cavity Radius of the 5 μ inch CLA Surface	41
18	Distribution of the Cavity Radius of the 4 μ inch CLA Surface	42
19	The Formation of Vapour Bubbles over Cavities in a Heated Surface	44
20	Conditions for the Entrapment of Gas	44
21	Bubble Nucleus at Cavity Mouth	48

22	Model for Temperature Profiles	48
23	Temperature Profile $\xi(\eta, \tau)$	51
24	Superheat Layer Thickness Correlations	53
25	Hsu Nucleation Model	55
26	Hsu Nucleation Model	56
27	Hsu Nucleation Model	57
28	Temperatures of Fluid and Bubble Near a Heating Surface	60
29	Han and Griffith Model	61
30	Han and Griffith Model	62
31	Han and Griffith Model	63
32	A Criterion for Incipient Boiling Condition	65
33	Cavity Size Distribution Function	68
34	Cavity Size Distribution	70
35	Griffith and Wallis Model	72
36	Nucleation Characteristics of the 16 μ inch CLA Surface	74
37	Nucleation Characteristics of the 5 μ inch CLA Surface	75
38	Nucleation Characteristics of the 4 μ inch CLA Surface	76
39	The Test Specimen and the Boundary Conditions	80
40	Finite Difference Method	82
41	Temperature Distribution in a Cylindrical Test Specimen	83
42	Boundary Conditions	85
43	Temperature Distribution Near the Boiling Surface	87
44	Modified Micholson Interferometer	89
45	A Typical Interferogram	91

46	A Typical Hole with Linear Temperature Drop	93
47	Normal Distribution of Temperature Measurements in a Hole	93
48	Representation of the Distributions in Holes and at Surface	96
49	The Uncertainty of the Temperature Measurements and the Correlated Slope	100

LIST OF TABLES

TABLE		PAGE
I	Test Conditions	30
II	Data of Saturated Boiling of Water	102
III	Observed Active Cavity Radii	104

CHAPTER I

INTRODUCTION

In recent years, boiling heat transfer has achieved world wide interest since it is the most efficient mode of heat transfer in use. Boiling heat transfer is defined as the mode of heat transfer that occurs with change of phase from liquid to vapour. Pool boiling is the type of boiling which occurs on a heating surface submerged in a pool of quiescent liquid. In pool boiling, when the surface temperature sufficiently exceeds the saturation temperature of the liquid, vapour bubbles form at specific locations on the surface. The bubbles grow rapidly in the superheated liquid layer adjacent to the surface until they depart and move out into the bulk liquid. Depending upon whether the liquid is subcooled or superheated, the bubbles will either collapse or continue growing.

Despite the extensive experimental and theoretical research into nucleation phenomenon, it is still not well understood. There are a number of proposed theories explaining nucleation phenomenon with regard to surface conditions and temperature fields, but none takes account of the nucleation characteristics of a boiling surface.

In the present work an attempt to study the activation of nucleation cavities is performed using the available nucleation theories. A discussion of the statistical distribution of the,

nucleation cavities is presented based upon the nucleate
boiling of water on a copper surface under saturation conditions.

CHAPTER II

LITERATURE SURVEY

In the process of nucleate pool boiling, it is quite conceivable that active nucleation sites differ from the remainder of the surface not only in their geometrical appearance but also in their wetting behaviour. It has also been shown [5, 14] that only cavities of narrow size range can be active nucleation sites. In order to correlate the nucleate pool boiling data, many models were postulated, but very few of them include the effect of surface conditions.

In 1936, Jakob [1] indicated qualitatively that for a given superheat, the rate of heat transfer increased as the macroscopic roughness increased, with the result that the surface finish could shift the position of the boiling curve markedly as shown in Figure 1 which was replotted in terms of heat flux versus wall superheat.

In 1952, Rohsenow [2] utilized the earlier observations by Fritz [3], concerning the relationship between the bubble departure frequency and departure size of the form $f D_b = \text{constant}$, to derive an equation in the form of

$$\frac{c_l (T_w - T_s)}{h_{fg}} = C_{sf} \left[\frac{q/A}{\mu_l h_{fg}} \sqrt{\frac{g_c \sigma}{g(\rho_l - \rho_v)}} \right]^{0.33} \left(\frac{\mu_l c_l}{k_l} \right)^{1.7} \quad (2.1)$$

where the coefficient C_{sf} varied with liquid-solid combination.

Curve No.	State of Heating Surface
1	Recently roughened by a sand blast
2	Same, oxidized by longer use
3	Same, roughened once more by sand blast
4	Same, after long use
5	Recently fitted with a roughness screen and cleaned
6	Same, after 4 hours of boiling, followed by 24 hours of lying in water
7	Same, after 8 more hours of boiling, followed by another 24 hours of lying in water

FIG. 1 EFFECT OF SURFACE ROUGHNESS ON THE BOILING
OF WATER

The first experiments specifically undertaken to investigate the effect of surface conditions were performed by Corty and Foust in 1955 [4], who showed a shift in the boiling curve to lower superheat with roughness increase. The superheat was plotted as a function of root mean square (RMS) roughness of the surface at constant heat flow rate as shown in Figure 2. It was shown that not only the position of the boiling curves but also their slopes varied with the surface roughness. In deriving an equation to correlate the pool boiling data, the authors postulated the existence of vapour trapped in conical cavities acting as the nuclei for bubble formation. The resulting equation was capable of predicting the radius of a stable nucleus as a function of the liquid properties as well as the contact angle and the conical angle of the cavity

$$\frac{2\sigma}{r_c P} \cos(\phi/2 - \theta) = \frac{h_{fg}(T_v - T_s)}{R T_v T_s} - \frac{2\sigma M}{r_c \bar{R} T_v \rho_v} \cos(\phi/2 - \theta) \quad (2.2)$$

It was apparent from this work that a large contact angle was better able to trap gas inside the cavity and consequently, such cavities had higher probability of being active.

In 1959, Clark, Streng and Westwater [5] showed that grain boundaries were not active nucleation sites in pool boiling by comparing the boiling data of ether on a polycrystalline zinc surface and on a single zinc crystal. It was also shown that the nucleation sites were not regions of special atomic density in the heating surface by an experiment

FIG. 2 SURFACE ROUGHNESS VS SURFACE SUPER-
HEAT AT CONSTANT h

in which single zinc crystal was aligned so that the heat transfer surface was the plane of maximum atomic density after which the results obtained with the aligned zinc crystal were compared with those of the polycrystalline zinc surface. The results of this experiment disagreed with those of Harrison [6] who boiled stearic acid from different faces of a single crystal of copper and found that the boiling curves for the different faces differed from one another. However, Clark et al. explained that Harrison had used surfaces which were prepared in contact with air, allowing the possibility that oxides had been formed which reacted chemically with the stearic acid, thereby affecting the chemical reactivity of the different crystal faces.

Bankhoff [7, 8] examined the mechanism of bubble nucleation in some detail and arrived at the conclusion that in boiling, bubbles originate from pre-existing vapour pockets in cavities on the surface. Bankhoff developed a mathematical model to predict the cavity radius corresponding to minimum superheat as

$$r_c = \left[\frac{4\mu_l k_l c_l \rho_l \sigma \cos\beta}{J^2} \left\{ \frac{T_v (v_v - v_l)}{h_{fg}} \right\}_{\text{avg.}}^2 \right]^{1/3} \quad (2.3)$$

Reasonable agreement with the literature was shown.

Kurihara and Myers [9] extensively studied the effect of surface roughness on nucleate boiling and submitted a set of boiling curves for different liquids boiled on copper surfaces of different surface finish. The authors correlated

the boiling data as a function of active site density, obtaining a correlation which showed that the mean coefficient of heat transfer is a function of the fluid properties and the number of active sites for all liquids and surface conditions

$$\frac{h}{k_l} = 820 \left(\frac{\rho_v}{\mu_l} \right)^{1/3} (N/A)^{1/3} (Pr)^{-0.89} \quad (2.4)$$

The heat flow rate per unit area q/A was shown to vary directly with the density of nucleation sites according to $(N/A)^m$, where the exponent m decreases as surface roughness increases contrary to Hatton and Hall [16] who showed that $q/A = \text{const.} (N/A)^{0.5}$ irrespective of the surface roughness. Kurihara and Myers also derived an equation relating the temperature difference and the surface conditions with the active site density

$$\frac{N}{A_1} - \frac{N}{A_2} = - \frac{C_1^*}{B} \int_{\Delta T_1}^{\Delta T_2} r^2 \beta(r) \exp \left(\frac{-E}{R} \right) d(\Delta T) \quad (2.5)$$

The equation cannot predict the active site density at a particular set of conditions but only predicts the difference in site density between two different conditions.

Griffith and Ellis [10] carried out extensive controlled experiments in which they investigated the nucleation properties of single artificial cavities formed in a copper surface and obtained boiling data for water, methanol and ethanol

on different copper surfaces finished with emery paper as well. The author showed that nucleation occurs from pre-existing gas-filled cavities on the surface. Furthermore, a single parameter $r_c = 2\sigma T_s / \rho_v h_{fg} (T_w - T_s)$, was sufficient to characterize such an active cavity since the surface superheat at which a cavity would become active was found to be fixed by the fluid properties. For a particular surface, a single plot of N/A versus $2\sigma T_s / \rho_v h_{fg} (T_w - T_s)$ was obtained. Consequently, it was concluded that the nucleation characteristics of a surface would be known if the size distribution of active sites on the surface were known. Griffith and Wallis also studied the stability of active sites and showed that the most stable cavities are those of reentrant type.

Gaertner and Westwater [11] utilized a novel electroplating technique to study the nucleation site population. By plating a thin layer of nickel, from an aqueous solution of nickel salts containing 20% solids, on a copper surface during boiling testing and subsequently counting the number of pin holes in the plate, they obtained nucleation site densities up to 1130 sites/sq. inch at $317,000 \text{ BTU}/(\text{hr. sq. ft.})$. The geometrical distribution of the active sites was found to be random and the heat flux was found to be approximately proportional to the square root of the active site density.

Gaertner did a further analysis upon his data and reported his results in reference [12]. The spatial distribution of the number of nucleation sites found in a local random area was correlated by a Poisson distribution and was represented

as a continuous distribution. This procedure is not correct as far as the statistical analysis is concerned since the Poisson distribution is discrete valued. The present author was able to correlate Gaertner's data with a Gamma distribution which is continuous valued. In addition, Gaertner developed an expression to predict the nucleation site density in the form of

$$\frac{N}{A} = N_0 \exp \left(- \frac{k}{T_w} \right) \quad (2.6)$$

where k is a function of the fluid properties. Later, Anderson, Judd and Merte [13] showed that, for a particular surface k is independent of the fluid properties.

Hsu [14] postulated a model for nucleation which implicitly limits the active cavity to those with favorable geometry of large depth to radius ratio. Assuming the existence of a limiting thermal layer of constant thickness, Hsu derived a mathematical model capable of predicting the maximum and minimum sizes of nucleation sites as a function of the surface temperature and the thermal layer thickness

$$r_{c \text{ min}} = \frac{\delta}{2C_1} \left[1 - \frac{\theta_s}{\theta_w} + \left\{ \left(1 - \frac{\theta_s}{\theta_w} \right)^2 - \frac{4AC_3}{\delta\theta_w} \right\}^{1/2} \right] \quad (2.7)$$

In comparing his model with existing data, the thermal layer thickness was estimated at one condition and then, using this estimated value, the theoretical and experimental results were compared for other conditions. Good agree-

ment was found especially at low values of saturation temperature. Hsu, also showed that the limiting value of the thermal layer thickness is dependent upon the turbulence.

Hall and Hatton [15] showed that the number of nucleation sites was directly dependent on the surface finish as measured by the center line average (CLA) value and that the heat transfer rate was predicted by the customary natural convection relation for all roughnesses until a critical site density was reached. Subsequently, in 1968 Vachon et al. [17] presented pool boiling data for mechanically polished and chemically etched 304 stainless steel surfaces with water at atmospheric pressure, for which the root mean square values of the surfaces were measured. It was shown that the boiling characteristic curves shifted to lower superheat with the increase of the root mean square roughness up to a certain value beyond which the boiling curve shifted to higher superheat. Contrary to Hall and Hatton [15], they concluded that the root mean square or the center line average was not adequate for the description of the surface condition as these values express the macroscopic surface preparation while nucleation is a function of the microscopic roughness. Also, Vachon et al. pointed out that a surface of similar roughness with different preparation techniques behaves differently with respect to boiling characteristics.

Han and Griffith [18] also studied the mechanism of heat transfer in nucleate pool boiling. Assuming the main mechanism of heat transfer in nucleate boiling to be transient

conduction to, and subsequent replacement of, the superheated layer around the nucleation sites, an expression for the wall superheat and the cavity radius for initiating bubble growth was developed.

$$r_{c \max} = \frac{\delta(T_w - T_s)}{3(T_w - T_\infty)} \left\{ 1 + \left[1 - \frac{12(T_w - T_\infty) T_s \sigma}{(T_w - T_s)^2 \delta \rho_v h_{fg}} \right]^{1/2} \right\} \quad (2.8)$$

Most of the proposed models for nucleation require knowledge of the superheated layer thickness which was lacking. Recently Wiebe and Judd [19] performed an experimental study with water boiling on a copper surface for heat flux q/A of 20,000, 50,000, and 100,000 BTU/hr. sq. ft. at various levels of subcooling ranging from 0°F to 105°F. They presented new data for temperature distributions adjacent to a heating surface for both saturated and subcooled boiling and determined the extrapolated superheat layer thickness. The superheated layer thickness δ was shown to decrease as the heat transfer coefficient h increased as shown in Figure 3. Also a relationship was shown to exist between the superheated layer thickness δ and the active site density N/A .

In reviewing the literature, it is clear that there is no reliable method existing for predicting within reasonable accuracy the nucleating characteristics of a heating surface.

FIG.3 SUPERHEAT LAYER THICKNESS CORRELATION

CHAPTER III

EXPERIMENTAL APPARATUS

3.1. Design Criteria

The apparatus was designed to be capable of:

1. Boiling water up to a maximum heat flux of 200,000 BTU/hr ft².
2. Obtaining unidirectional heat flow normal to the boiling surface.
3. Maintaining the bulk liquid at saturation condition.
4. Allowing the observation of active nucleation sites on the boiling surface with reasonable magnification by means of a microscope.
5. Accurately determining of the active site locations with the capability of relocating them.
6. Photographing the surface at the active site locations previously determined during the boiling process using high magnification.

3.2. Test Assembly

A sectional view of the test assembly is shown in Figure 4. The test assembly was comprised of a plexiglass vessel surrounding a cylindrical copper test specimen on the upper surface of which boiling was to take place. The copper test specimen was 3.1 inch long, 1.0 inch diameter at the boiling surface and 0.7 inch diameter at the other end.

FIG 4 SECTIONAL VIEW OF TEST ASSEMBLY

A 400 watt cartridge heater (Watlow Electronic) was inserted inside the test specimen in a cylindrical hole approximately $3/8$ inch diameter by 2 inches long machined to fit the heater. A stainless-steel sleeve 6 inches long, 1.0 inch outer diameter and reduced to 0.05 inch wall thickness at the upper end was epoxied to the test specimen thereby creating a 0.1 inch thick air gap between the specimen and the sleeve which was to serve as an insulating layer.

A plexiglass vessel 3 inches long by 4 inches outer diameter by 0.25 inch wall thickness, was press fitted on the stainless-steel sleeve by means of two "O" sealing rings which provided a water tight joint. The vessel was covered by a plexiglass cover $1/8$ inch thick, which was provided with an opening at its center to receive the microscope. The cover was allowed to float on the plexiglass vessel so that the cover did not move when the rest of the test assembly was moved.

3.3. Nucleation Site Locating System

The test assembly was mounted on an x-y stage provided with two micrometers capable of reading ± 0.0001 inch. The x-y stage itself was fixed to a stationary frame by three bolts. The stage provided a controlled and accurate travel of the whole test assembly in two normal directions.

A microscope with a focussing telescope and beam splitting prism was fixed vertically to the stationary frame by means of a rack and worm gear which provided vertical motion

of the microscope tube for coarse focussing. Fine focussing was provided by a cam mechanism. Various interchangeable eye pieces and objective lenses were used in the investigation to obtain the most favourable view of the boiling phenomenon occurring at the upper surface of the copper test specimen. The microscope together with the x-y stage were used to locate the active sites by moving the apparent nucleation sites to the center of the microscope field of view and reading the corresponding values of x and y. Figure 5 shows the test assembly, the x-y stage and the microscope.

3.4. Photographic System

Figure 6 shows the photographic system mounted above the test assembly with the plexiglass vessel moved out of the way. A polaroid camera has been mounted on the microscope. Two arms, fixed to the stationary frame by a vertical adjusting screw, were used to accept the camera and to prevent its weight from being transferred to the microscope. The vertical adjusting screw provided a vertical motion of the two arms which enabled the camera to be precisely positioned with respect to the microscope. This practice was adopted after it had been shown that loading the camera directly on the microscope created undesirable vibrations which disturbed the photography.

During the photographing, the objective lens of the microscope was replaced by a Watson 16 mm interference objective which is a microscope objective lens with a built-in

Legend

FIGURES 5, 6 and 11

- a Stainless steel sleeve
- b X-Y stage
- c Plexiglass vessel
- d Microscope
- e Circulating pump
- f Polaroid camera
- g Interference objective
- h Potentiometer
- i Control unit
- j Lamp
- k Power supply

Fig. 5 Nucleation Site Locating System

Fig. 6 Photographic System

interferometer for the examination of surfaces by reflected light. The monochromatic light required for the interference investigation was provided by a Osram Hg 10 mercury spectral lamp connected to a power supply (Spectronics model 1500).

3.5. Regulatory Systems

(i) Water Circulating System

To keep the water above the boiling surface at the saturation temperature for the duration of the tests, the water was heated in a stainless-steel beaker set on a plate heater. A small variable speed centrifugal pump was used to circulate the water to the plexiglass vessel and back to the beaker. The flow of water was always set at the minimum possible value attainable in order to minimize the influence of forced convection.

(ii) Condensing System

A condenser was constructed of one turn of a 1/4 inch diameter copper tube with approximately 16 square inches of cooling surface suspended from the cover plate. Cold water from the mains was passed through it in order to return the vapour phase to the liquid phase in order to minimize water replacement which would have adversely affected the temperature levels in the vessel.

(iii) Demisting System

Compressed air passing through a 1/16 inch diameter stainless-steel tube was used to get rid of the condensed vapour on the microscope objective lens. The stainless-steel tube was fixed to the cover plate by a Swagelok fitting. The tube was bent to direct the air stream against the objective lens, as can be seen in Figure 4, without disturbing the water in the plexiglass vessel.

3.6. Temperature Measuring System

Three 30 gauge fiberglass insulated chromel constantan thermocouples were used to measure the temperature of the copper test specimen at three locations on the center line, 1/8, 7/16 and 3/4 inch from the boiling surface. Three holes 1/16 inch diameter each were drilled in the copper specimen as shown in Figure 7. The bare thermocouple wires were passed through a 1/16 inch diameter, two-hole ceramic insulator. A drop of epoxy glue was used to hold the wires in place, as indicated in Figure 8. The thermocouple junction was formed at the end of the ceramic insulator. The insulators carrying the thermocouple wires were fitted in the drilled holes in the test specimen.

A fourth 36 gauge nylon insulated chromel constantan thermocouple was used to measure the water temperature. The thermocouple was passed through a 1/16 inch diameter stainless-steel tube and a drop of epoxy glue was used to fix the thermocouple junction at the end. The stainless-steel tube was fixed

FIG. 7 THERMOCOUPLE LOCATIONS

FIG. 8 THERMOCOUPLE ASSEMBLY

to the cover plate by a Swagelok fitting as shown in Figure 4.

A typical thermocouple circuit is shown in Figure 9.

To conserve chromel constantan wire, a transition was made to single strand nylon insulated thermocouple grade copper wire at the ice baths in all thermocouple circuits. The leads were connected to copper knife switches which directed the output signal to a Honeywell potentiometer (Model #2745, Serial # 109178) capable of reading with an accuracy of $\pm .005$ millivolt.

3.7. Power and Control

The power was supplied to the cartridge heater by a 240 volt, 10 ampere variac. A wattmeter (Conway Electronics # 3303240) was used to measure the power. A 115 volt, 2.5 ampere variac regulated the power to the circulating pump. The schematic power control circuit is shown in Figure 10. The control unit seen together with the complete test assembly in Figure 11 was constructed to house the variacs, the thermocouple knife switches, the wattmeter and the ice baths.

FIG. 9 THERMOCOUPLE CIRCUIT

FIG 10 POWER CIRCUIT DIAGRAM

Fig. 11 Experimental Arrangements

CHAPTER IV

TEST CONDITIONS

The investigation was carried out at standard atmospheric pressure upon the same copper test specimen with three different surface finishes.

1. A standard machine shop finished surface having a 16 micro-inch center line average finish as indicated by the Talysurface profile as shown in Figure 12.a. Before this surface was tested it had been subjected to various boiling processes over a period of three months during the preliminary preparation of this experimental study, during which time a hard coating had been deposited on the surface.
2. A fine machined surface having a 5 micro-inch center line average finish as indicated by the Talysurface profile shown in Figure 12.b. This surface was prepared by machining on a lathe with a sharpened oil stoned tool using extra fine feed to obtain the smoothest mechanically finished surface which the machine shop was capable of producing.
3. A mirror polished surface which was produced in the Metallurgical Engineering Department laboratories using six micron and then one micron diamond pastes as the polishing medium with kerosene lubricant, having a 4 micro-inch

(a) 16 μ inch CLA (b) 5 μ inch CLA (c) 4 μ inch CLA

FIG 12. TALYSURF PROFILES OF THE THREE SURFACES.

center line average finish as indicated by the Talysurf profile shown in Figure 12.c.

For each of the three surface finishes, saturated boiling tests were carried out in which the water bulk temperature was kept at the saturation condition. The boiling tests were carried out with decreasing heat flux from a heat flux level of about 150,000 BTU/hr. sq. ft., the maximum obtainable with the test apparatus. Although heat flux and surface superheat were measured up to this limit, the observation of the individual nucleation active sites was possible only up to 60,000 BTU/hr. sq. ft. and consequently the nucleation site density was obtainable up to only this limit. An investigation of the nucleation sites, to obtain the size and distribution of the nucleation sites, was carried out at three levels of heat flux, for each surface, selected to cover the range of heat flux from 20,000 to 60,000 BTU/hr. sq. ft. The test conditions are tabulated in Table 1.

TABLE I

No.	Surface Finish	No. of Tests	Heat Flux Range BTU/hr.sq.ft.		Nucleation Site Investigation	
			Minimum	Maximum	No. of Tests	Heat Flux BTU/hr.sq.ft.
1	16 μ inch CLA	19	18,389	140,619	3	28,313 38,219 52,994
2	5 μ inch CLA	11	30,000	141,104	3	31,060 35,798 38,000
3	4 μ inch CLA	21	16,895	134,696	3	29,308 36,159 41,516

CHAPTER V

TEST PROCEDURE

The apparatus was filled with distilled water and then the cartridge heater and the circulating pump were turned on. The plate heater was set to heat the distilled water to the saturation temperature in the stainless-steel beaker external to the test assembly. The speed of the circulating pump was adjusted by the variac to control the water level in the test assembly about one inch above the boiling surface. Then, the condenser cooling water and the air supply were turned on. The air flow rate was adjusted to the minimum value capable of removing the condensed vapour from the surface of the microscope objective lens.

To assure that the nucleation sites were properly activated at the beginning of each test, the power level was adjusted to a higher value than that required for the test for about thirty minutes and then reduced gradually to the required level. Once the heat flux was changed to a new value, it took about 45 minutes for the system to regain thermal equilibrium.

The attainment of thermal equilibrium was indicated by invariant measurements of the three thermocouples at the specimen center line and the temperature of the bulk water. It was found that the water bulk temperature was sensitive to

the condenser cooling water flow rate, especially at low levels of heat flux. Consequently, care was taken to adjust the cooling water flow rate to minimize the interdependence.

Once conditions had attained steady state, the individual temperatures at the three locations on the specimen center line and the water bulk temperature were measured by the Honeywell potentiometer. The individual temperatures were measured three times at 10 minute time intervals and the average of each set of measurements was recorded. The three temperature measurements at the specimen center line were linearly correlated by the least square method and the correlated slope was used, together with the known value of copper thermal conductivity to evaluate the heat flow rate normal to the boiling surface. The surface temperature was determined by extrapolating the correlation line to the boiling surface.

Using the microscope with 15x overall magnification (5 x eye piece and 3 x objective lens), the vapour bubbles were observed. The microscope field of view was 0.1 inch diameter at this level of magnification. The number of nucleation sites in the microscope field of view at four or five different locations chosen arbitrarily were counted and their locations were determined using the x-y stage. The average nucleation site density at this particular condition of heat flux and surface temperature was determined.

For the purpose of the nucleation site investigation, each nucleation site was moved to the center of the cross in the focussing telescope by means of the x-y stage and the

corresponding readings of the two micrometers were recorded.

After locating the nucleation sites, the experiment was stopped, the surface was dried and the plexiglass vessel was moved out of the way. The eye piece was replaced by a 12 x magnification lens and the objective lens was replaced by the Watson interference objective having 10 x magnification making the overall magnification 120 x. Then, the camera was mounted on the supporting arms and adjusted in place with respect to the microscope tube.

By resetting the x-y stage to the previously determined coordinates it was possible to relocate the nucleation sites. To avoid any discrepancy in relocating the nucleation cavities, a fine dot was made at the center of the boiling surface. Before photographing, the center dot was relocated to be sure that its coordinates had not been changed inadvertently.

The Watson interference objective provided the possibility of obtaining photomicrographs or interferograms by means of a simple adjustment. Consequently, the polaroid camera could be used to photograph either condition. The active cavities were distinguished by the shape of the interference fringes around them and by the concentric fringes indicating different levels of depth of the cavity within them as shown in Appendix B. For the purpose of the present investigation, it was sufficient to work with photomicrographs, so that the interferogram shown was only obtained for academic reasons. The photomicrographs of the nucleation sites were

then examined using the Measurescope (Nikon # V8494) in order to measure the average radius of the nucleation cavities. Most of the observed cavities had approximately circular mouths; the very few scratches observed were excluded.

For each level of heat flux, the minimum and maximum radii of the observed nucleation sites were determined and the statistical distribution of the active site radius was examined. A histogram of the relative frequencies of occurrence was constructed to obtain the active site distribution as a function of the radius. It was possible to construct the histogram using either natural or logarithmic intervals of the nucleation site radii without affecting the validity of the data; it subsequently proved to be more convenient to work in terms of the logarithmic intervals and consequently the data leading to the results presented in the next section was treated in this way.

CHAPTER VI

RESULTS

In this chapter, the experimental data is presented with little comment. Analysis of the data is presented in Chapter VII. Both the experimental and calculated data are tabulated in Appendix E.

Figure 13 shows a plot of heat flux q/A as a function of surface superheat $(T_w - T_s)$ for the three different surface conditions. It is apparent that decreasing surface roughness has shifted the boiling curve to higher superheat for the same heat flux.

Figure 14 shows a plot of the total nucleation site density N/A as a function of the surface superheat $(T_w - T_s)$. It is seen that the results can be represented according to $(N/A) = a (T_w - T_s)^b$. It is apparent that a small increase in surface superheat can result in a large increase in total nucleation site density. Increasing surface roughness results in more nucleation sites for the same superheat. Furthermore, the slope of the curve increases with the decrease of surface roughness.

Figure 15 represents the relationship between the total site density N/A and the heat flux q/A for the three surfaces. The resulting curves appear to be parallel with a slope of about 2, which agrees with the correlation proposed

FIG. 13 BOILING CHARACTERISTIC CURVES

FIG. 14 NUCLEATION SITE DENSITY VS SURFACE SUPERHEAT

FIG-15 NUCLEATION SITE DENSITY VS THE HEAT FLUX

by Hatton and Hall [16], $q/A \propto (N/A)^{0.5}$ and disagrees with the correlation of Kurihara and Myers [9] who observed a change of slope with a change of surface roughness.

Figures 16, 17 and 18 present the distribution of the nucleation cavity radius for the three surfaces tested at three levels of heat flux each as indicated by plots of the frequency of occurrence per unit surface area with respect to cavity radius.

FIG. 16 DISTRIBUTION OF THE CAVITY RADIUS OF THE $16 \mu\text{in. CLA SURFACE}$

FREQUENCY OF OCCURRENCE OF NUCLEATION SITE DENSITY (N/A)

FIG-17 DISTRIBUTION OF THE CAVITY RADIUS OF THE $5 \mu \text{ In. CLA SURFACE}$

FIG 18 DISTRIBUTION OF THE CAVITY RADIUS OF THE μ in C L A SURFACE

CHAPTER VII

ANALYSIS AND DISCUSSION

In carefully cleaned test systems, heating of a pure liquid can produce high levels of superheat up to a limit of stability where homogeneous nucleation and vapour formation take place. However, for the case of heat transfer associated with heterogeneous boiling at solid heating surfaces, the surface temperatures at which nucleation takes place are very much smaller than these. Casual observations of nucleate boiling show bubble streams originating from specific locations on the surface; microscopic observation of these locations reveals a cavity or a scratch where a bubble formed. Corty and Foust [4], Bankhoff [8, 20] and others developed the postulate that bubbles at a heating surface originate from cavities in which a gas or a vapour phase pre-exists as shown in the following figure. As heat is added, more vapour forms in the cavity as shown in Figure 19.a, and a bubble forms and departs as shown in Figure 19.b, after which liquid closes in over the cavity trapping vapour which is the nucleus for the next bubble. Two cases of different contact angle and opposite curvature of the interface may be considered. In Figure 19.c, $P_v > P_l$ since the surface has been allowed to cool below the saturation temperature of the liquid so that the cavity will collapse. In Figure 19.d, $P_v < P_l$ and therefore the trapped vapour can withstand subcooling of the

FIG. 19 THE FORMATION OF VAPOUR BUBBLES OVER CAVITIES IN A HEATED SURFACE

FIG. 20 CONDITIONS FOR THE ENTRAPMENT OF GAS IN THE ADVANCE OF A LIQUID LAYER ACROSS A GROOVE

liquid; the nucleus can be activated again when the surface is subsequently reheated. Therefore, the problem of nucleation can be resolved into three parts: one, the conditions necessary to entrap vapour or gas into surface cavities; two, the stability of a cavity containing entrapped gas or vapour; three, the conditions that govern the formation of a bubble from an active cavity with entrapped vapour. The first part was investigated by Bankhoff [20]; who presented criteria for the entrapment of gas in a surface cavity as shown in Figure 20. From the figure one can conclude that for the advance of semi-infinite liquid layer across a V-shaped profile groove or cavity, the condition for entrapment of gas is that $\theta > \phi$. A discussion of the second part can be found in references [4], [7], [8] and [10] in which it was generally concluded that cavities of larger contact angle and having large depth to width ratio are more stable. With respect to the third part, all of the investigators are in agreement about the criterion for bubble growth which is that the thermal layer surrounding the nucleus must be at a mean temperature equal to or greater than the temperature of the vapour in the nucleus. This condition allows an inward flow of heat from the superheated thermal layer to the bubble through the nucleus wall.

Before the growth begins, the bubble is in a condition of thermostatic equilibrium. The equation describing this condition is,

$$P_v - P_l = \frac{2\sigma}{r} \quad (7.1)$$

The Clausius-Clapeyron relationship is introduced

$$\frac{dP}{dT} = \frac{h_{fg}}{v_{fg} T} \quad (7.2)$$

which is approximated in the form

$$\frac{P_v - P_l}{T_v - T_s} = \frac{h_{fg} \rho_v}{T_s} \quad (7.3)$$

Solving Equations (7.1) and (7.3) to eliminate $(P_v - P_l)$, one obtains

$$T_v = T_s + \frac{2\sigma T_s}{r \rho_v h_{fg}} \quad (7.4)$$

Assuming that the bubble is in thermal equilibrium and $T_v = T_w$. This mathematical relationship represents an approximate expression for the superheat required for equilibrium of a nucleus of radius r . Nuclei of radius greater than r predicted by Equation (7.4) should become bubbles and grow; those of smaller radius should collapse.

Griffith and Wallis [10] used this approach to predict the surface temperature required to start the bubbles growing from a cavity of mouth radius r_c ,

$$r_c = 2\sigma T_s / [\rho_v h_{fg} (T_w - T_s)] \quad (7.5)$$

In an attempt to incorporate the temperature distribution in the superheated thermal layer adjacent to the surface into an expression for predicting nucleation conditions, two models were proposed by Hsu [14] and by Han and Griffith [18]

respectively. Both models assumed that the principle mechanism by which nucleation cavities were activated was transient conduction to, and subsequent replacement of the superheated thermal layer around the nucleation cavities. An outline of the two models follows.

Hsu Model

Hsu assumed the existence of a bubble nucleus sitting at the mouth of a cavity as depicted in Figure 21. At the beginning of a bubble cycle, relatively cool bulk liquid at temperature T_∞ surrounds the nucleus. As the time passes, the cool liquid is warmed up by the transient conduction process, and the thermal layer grows. This thermal layer however, cannot grow indefinitely. Hsu assumed the existence of a limiting thermal layer of constant thickness δ such that for $y < \delta$ molecular transport prevails while for $y \geq \delta$ the temperature remains at T_∞ since turbulence is responsible for the transport of energy. The mathematical expression for the transient conduction phenomenon is,

$$\frac{\partial^2 \theta}{\partial x^2} = \frac{1}{\alpha} \frac{\partial \theta}{\partial t} \quad (7.6)$$

The initial condition is $\theta(x, 0) = 0$ and the boundary conditions are $\theta(0, t) = \theta_w$ and $\theta(\delta, t) = 0$ respectively. The temperature profile satisfying such an equation is

$$\xi = \frac{\theta}{\theta_w} = \eta + \frac{2}{\pi} \sum_{n=1}^{\infty} \frac{\cos n \pi}{n} \sin n \pi \eta \cdot \exp(-n^2 \pi^2 \tau) \quad (7.7)$$

FIG. 21 BUBBLE NUCLEUS AT CAVITY MOUTH

FIG. 22 MODEL FOR TEMPERATURE PROFILES

where $\tau = \alpha t / \delta^2$ and $\eta = x / \delta$ are dimensionless time and space parameters.

The bubble nucleus will not grow unless the surrounding liquid is warmer than the vapour in the bubble. The end of the waiting period is reached when $\theta(x,t)$ equals θ_b at some arbitrary distance b above the boiling surface. The history of the waiting period is depicted by Figure 22 a, b and c. Figure 22a shows the temperature profile at the beginning of the waiting period. Figure 22b represents the situation during the waiting period. Figure 22c shows the end of the waiting period when the liquid temperature distribution passes the point (θ_b, x_b) . Assuming the temperature within the nucleus can be found by applying Equation (7.4) written in the form

$$\theta_b = \theta_s + \frac{2\sigma T_s}{r_n \rho_v h_{fg}} \quad (7.8)$$

and considering the nucleus to be a truncated sphere as depicted in Figure 21, then simple geometry yields

$$b = \left(\frac{1 + \cos\beta}{\sin\beta} \right) r_c = c_1 r_c \quad c_1 = \left(\frac{1 + \cos\beta}{\sin\beta} \right)$$

$$r_n = \frac{r_c}{\sin\beta} = c_2 r_c \quad c_2 = \frac{1}{\sin\beta}$$

$$r_n = \frac{b}{c_3} \quad c_3 = \frac{c_1}{c_2}$$

Then, applying the condition which prevails at the end of the

waiting period

$$r_n = \frac{\delta - x_b}{c_3} \quad (7.9)$$

and combining Equations (7.8) and (7.9), Hsu obtained

$$\theta_b = \theta_s + \frac{2\sigma T_s}{\rho_v h_{fg} [(\delta - x_b)/c_3]} \quad (7.10)$$

which can be written in dimensionless form,

$$\begin{aligned} \xi_b = \frac{\theta_b}{\theta_w} &= \xi_s + \frac{2\sigma T_s c_3}{\rho_v h_{fg} \delta \theta_w} [1/(1-\eta_b)] \\ &= \xi_s + \frac{A c_3}{\delta \theta_w} [1/(1-\eta_b)] \end{aligned} \quad (7.11)$$

where $A = \frac{2\sigma T_s}{\rho_v h_{fg}}$ is a dimensionless fluid property parameter.

Whenever Equation (7.11) is satisfied the waiting period ends and the nucleus begins to grow. Figure 23 shows the temperature profiles given by Equation (7.7) plotted in the dimensionless form, ξ against η , with τ as a parameter. Those cavities having infinitely long waiting periods are inactive. The intersection points of the criterion curve, ξ_b against η_b , with the line $\xi = \eta$ are designated as A and B. Those cavities with η_b falling within these limits have finite waiting periods and thus could be active nucleation cavities according to thermodynamic considerations.

Substituting for $\xi_b = \eta_b$ into Equation (7.11) and solving for r_c , Hsu obtained

$$F(\eta_b) = \xi_b + \frac{A c_3}{\delta \theta_w} [1 / (1 - \eta_b)]$$

$$\psi(\eta, \tau) = \eta + \frac{2}{\pi} \sum_{n=1}^{\infty} \frac{\cos n\pi}{n} \sin n\pi\eta \cdot \exp(-n^2 \pi^2 \tau)$$

$$\tau = \frac{\alpha t}{\delta^2}$$

FIG. 23 TEMPERATURE PROFILE $\xi(\eta, \tau)$

$$r_{c \min.} = \frac{\delta}{2c_1} \left[1 - \frac{\theta_s}{\theta_w} + \left\{ \left(1 - \frac{\theta_s}{\theta_w} \right)^2 - \frac{4\Lambda c_3}{\delta \theta_w} \right\}^{1/2} \right] \quad (7.12)$$

According to Equation (7.12), no cavity will be active if the discriminant is negative, i.e.

$$\left[\left(1 - \frac{\theta_s}{\theta_w} \right)^2 - \frac{4\Lambda c_3}{\delta \theta_w} \right] < 0 \quad (7.13)$$

which enabled Hsu to derive a criterion for incipience, the condition at which the first cavity nucleates.

For saturated boiling, the incipience criterion as predicted by Equation (7.13) becomes

$$\theta_{w_0} = 4\Lambda c_3 / \delta_0 \quad (7.14)$$

and Equation (7.12) then reduces to

$$r_{c \min.} = \frac{\delta}{2c_1} \left[1 + \left\{ 1 - \frac{4\Lambda c_3}{\delta \theta_w} \right\}^{1/2} \right] \quad (7.15)$$

Hsu assumed the thermal layer thickness δ to be constant due to the lack of information about the thermal layer thickness. It has been shown by Wiebe and Judd [19] that the thermal layer thickness is not constant but changes as indicated in Figure 24. From the same figure it is apparent that the extrapolated layer thickness at the incipient condition δ_0 is approximately constant for different levels of subcooling and equal to about 0.0275 inches. In order to utilize the Hsu model to compare with the experimental data from the present investigation, δ was assumed to vary according

FIG. 2.4 SUPERHEAT LAYER THICKNESS CORRELATION

to Figure 24 and the contact angle θ was assumed to be 70° in accordance with measurements of Rao [23] who reported values of contact angle from 66° to 72° for copper surfaces. The thermal layer thickness at incipience δ_0 was assumed constant 0.0275 inches as indicated by Wiebe and Judd [19]. This assumption is justified by arguing that before boiling starts the thermal layer thickness is established by turbulent natural convection which is not affected by the surface conditions. By plotting the cavity radius r_c predicted by Equation (7.15) for the three surfaces tested against superheat θ_w , Figures 25, 26 and 27 were obtained. The minimum and maximum radii of active cavities observed experimentally at three levels of surface superheat for each surface has been superimposed for the sake of comparison. The measured results tend to fall along the lower branch of the curve. This observation can be explained qualitatively. In spite of the wide range of nucleation cavity radii which could be activated according to the Hsu model, cavities of large radii were not active on the surfaces tested because the smaller cavities exist in larger numbers than the larger cavities and apparently are better able to hold a residue of vapour and be activated by their neighbours. Under what conditions an active cavity is able to activate another one, cannot be answered at the time being and needs further study.

No cavities having radii in the vicinity of the upper branch of the curve were observed to be active, either because the conditions required for cavity activation relating to the

FIG. 25 HSU NUCLEATION MODEL

FIG. 26 HSU NUCLEATION MODEL

FIG. 27 HSU NUCLEATION MODEL

retention of a vapour residue were not established or cavities of these large radii did not exist on the tested surfaces.

De [22] investigated nucleation from an artificial cavity of 0.0042 inch radius which is relatively large as compared to the cavity radii observed in the present work but falls within the range predicted by Hsu's model. Subsequently, De confirmed that the activation of relatively large cavities is possible if the right conditions were established.

Han and Griffith Model

Using the same transient conduction mechanism, Han and Griffith [18] solved the conduction equation for the same initial condition and the first boundary condition specified by Hsu. The second boundary condition used was $\theta(\infty, t) = 0$. The temperature profile in the liquid adjacent to the surface satisfying the differential equation was

$$\theta(x, t) = \theta_w \operatorname{erfc} \frac{x}{2\sqrt{\alpha t}} \quad (7.16)$$

from which the gradient at the wall is given by

$$\left(\frac{\partial \theta}{\partial x} \right)_{x=0} = - \frac{\theta_w}{\sqrt{\pi \alpha t}} \quad (7.17)$$

Assuming the temperature distribution at any instant to vary linearly from the wall to $x = \delta$, the thickness of the thermal layer is required from the above equation to be,

$$\delta = (\pi \alpha t)^{1/2} \quad (7.18)$$

During the initial period of growth, the bubble was treated as an insulated hemisphere of radius r_c . From the potential flow theory and fluid flow analogy, the distance of an isothermal line passing through the top point of a waiting nucleus was established to exist $3/2 r_c$ from the heating surface when measured on the flat portion of the isothermal line as shown in Figure 28. The liquid temperature at this point is given by

$$T_{0L} = T_w \left[1 - \frac{3r_c}{2\delta} \right] \quad (7.19)$$

Equating this liquid temperature with that required to activate the bubble from Equation (7.4) or (7.8) and solving for r_c , Han and Griffith obtained

$$r_{c \min} = \frac{\delta (T_w - T_s)}{3T_w} \left[1 + \left\{ 1 - \frac{6A\theta_w}{(T_w - T_s)^2 \delta} \right\}^{1/2} \right] \quad (7.20)$$

According to Han and Griffith's model, the thermal layer thickness δ varies with the wall superheat. Using Judd and Wiebe's superheat layer thickness measurements, the cavity radius r_c predicted by Equation (7.2) was plotted as a function of superheat θ_w in Figures 29, 30 and 31 along with the relationship recommended by Griffith and Wallis [10] for the minimum nucleation cavity radius as obtained by Equation (7.5). The experimental results were superimposed for comparison. It is apparent that the curve representing the Griffith and Wallis model is asymptotic to the lower branch of the curve. The tendency of the data to fall along the lower branch of the curve is apparent as in the Hsu model.

FIG. 28 TEMPERATURES OF FLUID AND BUBBLE NEAR A HEATING SURFACE.

FIG. 29 HAN AND GRIFFITH MODEL

FIG. 30 HAN AND GRIFFITH MODEL

FIG. 31 HAN AND GRIFITH MODEL

It is a matter of some importance to discuss the incipience phenomenon. Incipient boiling is the condition at which the first cavity nucleates. As illustrated in Figure 32, incipience is the condition which exists at time $t = \infty$ when the steady state temperature profile in the thermal layer adjacent to the surface is just tangent to the criterion curve as predicted by Equation (7.4). Provided that cavities of that particular radius exist having a residue of gas or vapour trapped within them, the first bubble will appear. However in many of the references, it would seem that the experimental observation of incipience did not occur until higher surface superheat than those predicted by any of the proposed models were attained. In the present work, the calculated surface superheat at incipience based upon the value of the incipient thermal layer thickness δ_0 obtained from reference [19] is about 0.5°F for both models investigated while no significant boiling was observed until surface superheat exceeded 10°F . This lack of agreement is most likely explained by the non-existence of sufficiently large cavities with the prerequisite residue of vapour. For example, in the present work the radius of the nucleation cavity that could be activated at 0.5°F superheat is of the order of 0.009 inches, while the maximum nucleation cavity radius observed to be active was 0.0006 inch. According to reference [22], De observed nucleation of a 0.0042 inch radius cavity artificially made on a copper surface at 1.9°F superheat under 1.4°F sub-cooling but this cavity was especially favoured since it was

FIG. 32 A CRITERION FOR INCIPIENT BOILING CONDITION

supplied with a continuous supply of vapour.

With regard to the nucleation phenomenon in pool boiling, both of the models proposed to predict the activation of nucleation cavities represent necessary but non-sufficient conditions for cavities to nucleate. In order to be able to predict the nucleation characteristics of a boiling surface, the active cavity distribution of the surface, the ability of the cavities to entrap vapour or gas and the stability of the cavities entrapping gas should also be known. As the nucleation characteristics of a surface is affected by the nucleation cavity size distribution which is strongly dependent on the microstructure of the surface, the surface roughness and type of surface preparation play an important role in controlling the nucleation on the boiling surface.

From Figures 14 and 15, it is apparent that the surfaces of smoother finish result in fewer nucleation sites for the same values of heat flux q/A and surface superheat θ_w , apparently because smoothing or polishing a surface may cause elimination of the larger nucleation cavities which could satisfy the thermodynamic conditions necessary to activate them and presumably changes the ability of the cavities to entrap vapour or gas residue. However, it is worthwhile to note here, that the nucleation characteristics of a surface is relatively insensitive to the surface macroroughness which can be measured with a Talysurf instrument but that it is rather a function of the microroughness of the boiling surface.

Griffith and Wallis obtained curves of nucleation

site density N/A as a function of the surface superheat $(T_w - T_s)$ for the boiling of three different liquids on a copper surface. The three curves were drawn together as a single curve in a plot of N/A against r_c in which r_c was determined by Equation (7.5). Similarly, Anderson and Judd [13] were able to draw their data together for boiling of seven different fluids on a glass surface into a single curve of N/A against the parameter group $[2\sigma T_s / \rho_v h_{fg}(T_w - T_s)]$. This treatment of the data shows that a single dimension of this form is sufficient to characterize such nucleation cavities in general.

The resulting single curve of active site density N/A against the parameter group $[2\sigma T_s / \rho_v h_{fg}(T_w - T_s)]$ represent the integral of a cavity distribution function such as that indicated in Figure 33, where for the particular surface at the particular boiling condition, the nucleation site density for cavities of radius equal to greater than r_c is defined as

$$(N/A)_{r_c} = - \int_{r_{c \max}}^{r_c} n \, dr_c \quad (7.21)$$

where $r_{c \max}$ is the maximum active cavity radius at this condition. The total site density is expressed as

$$(N/A) = - \int_{r_{c \max}}^{r_{c \min}} n \, dr_c \quad (7.22)$$

which is the area under the distribution curve between the minimum and maximum active cavity radii at this condition.

FIG-33 CAVITY SIZE DISTRIBUTION FUNCTION

Brown [24] suggested that the site density $(N/A)_{r_c}$ of nucleation cavities of radius greater than or equal to r_c could be correlated with according to

$$(N/A)_{r_c} \propto \left(\frac{1}{r_c}\right)^m \quad (7.23)$$

This equation will yield the total active site density if the minimum active cavity radius $r_{c_{min}}$ is substituted. This relationship was examined in the present investigation. For each surface tested at each level of heat flux and surface superheat, the nucleation cavities and their radii were examined. The range of nucleation cavity radius observed was divided into constant intervals on the logarithmic scale and for each interval the corresponding number of nucleation cavities per unit area equal to or larger than the radius at this interval was recorded and plotted in the manner suggested by Equation (7.23) for each surface at each of the three levels of heat flux. The correlations shown in Figure 34 were obtained. It is observed that single correlation was obtained independent of the heat flux. The darkened symbols in Figure 34 indicate the total active site density corresponding to the minimum observed cavity radius at the particular level of heat flux. It is reasonable that a correlation of these darkened symbols only should yield the same relationship, since this treatment of the data is conceptually the same idea proposed by Griffith and Wallis. Their correlation of (N/A) against the cavity radius r_c predicted by Equation (7.5) represents the relationship which would be obtained by correlating the

FIG. 34 CAVITY SIZE DISTRIBUTION

darkened symbols in Figure 34. From Figure 34, one can conclude that the smoother the surface the more the correlation of $(N/A)_{r_c}$ versus r_c shifts to the left on the graph indicating a decrease in the number of nucleation cavities of the same cavity radius. Also, the exponent m of the correlation relationship appears to vary slightly, having a tendency to increase with the smoothness of the surface. The exponent m appears to be a function of the nucleation cavity size distribution and, consequently should be considered with any proposed model for predicting the boiling characteristics of a surface.

The ability of the parameter group $[2\sigma T_b / \rho_v h_{fg} (T_w - T_b)]$ to represent the minimum nucleation cavity radius is confirmed by Figure 35. The data points on the graph are the darkened symbols on Figure 34. Good agreement is observed indicating the possibility of using such a group to predict the minimum active cavity radius rather than determining it experimentally. In this way, surface nucleation characteristics could be derived by correlating (N/A) versus $r_{c_{min}}$ rather than by correlating $(N/A)_{r_c}$ versus r_c as was done in the present investigation, with considerable saving of effort.

In investigating the statistical distribution of cavity radius from Figures 16, 17 and 18, no known statistical distribution was capable of fitting these distributions. The only consistent feature of these distributions is that for the increase of heat flux or surface superheat the mean of the distribution moves to lower values of cavity radii indicating

FIG. 35 GRIFFITH AND WALLIS MODEL

that with the increase of heat flux or wall superheat, smaller cavities are activated.

It was decided to generate a three-dimensional plot of surface superheat θ_w , nucleation cavity radius r_c and the frequency of occurrence of nucleation cavity density $f(N/A)_{r_c}$ as shown in Figures 36, 37 and 38 using the Han and Griffith model for comparison. For each plot, it is clear that for the same surface the area under the distribution curve is increasing with the increase of the surface superheat, indicating the increase of the total number of active nucleation cavities (N/A) . Also, the shift of each distribution curve to lower radii with the increase of the surface superheat is clear. Such a three-dimensional plot can characterize the nucleation behaviour of boiling surface under particular boiling conditions.

FIG 36 NUCLEATION CHARACTERISTICS OF THE 16 μ in CLA SURFACE

FIG. 37 NUCLEATION CHARACTERISTICS OF THE 5 μ in CLA SURFACE

FIG. 38 NUCLEATION CHARACTERISTICS OF THE 4μ CLA SURFACE

CHAPTER VIII

CONCLUSIONS

1. The investigation presents a set of measurements of saturated nucleate boiling of water on a copper surface with three different surface finishes.
2. Two models for nucleate boiling proposed by Hsu and Han and Griffith were used to compare with the nucleation cavity radii measured. The experimental data were in agreement with the two models examined with a tendency to fall in the lower portion of the predicted range of cavity radii.
3. The models for predicting the activation of nucleation cavities examined represent necessary but non-sufficient conditions for cavities to nucleate since some cavities that satisfy these models were observed not to nucleate under certain conditions.
4. Apparently, small cavities are better able to entrap vapour residue and be activated by their neighbours since few of the larger cavities were observed to nucleate.
5. Incipience was observed at higher superheat than that predicted by either model examined because of the non-existence of sufficiently large cavities, with the prerequisite residue of vapour.

6. The analysis performed is consistent with Weibo and Judd's superheat layer thickness measurements indirectly, since the agreement obtained could not have been attained if these results were grossly in error.
7. The relationship recommended by Brown to correlate $(N/A)_{r_c}$ as a function of r_c was found to fit the data.
8. The parameter group $[2\sigma T_s / \rho_v h_{fg} (T_w - T_s)]$ is in general capable of predicting the minimum nucleation cavity radius and therefore the usage of this parameter group with Brown's correlation is recommended as a sufficient method describing the boiling nucleation characteristics.

APPENDIX A

ANALYSIS OF THE UNIDIRECTIONALITY OF HEAT FLOW

One of the important design criteria was to ensure the unidirectionality of heat flow normal to the boiling surface. In the early stages of the design of the copper test specimen, the configuration was chosen to be a cylindrical form, 1 inch in diameter and 3.1 inches long with a cylindrical hole to accept a cartridge heater 3/8 inches diameter by 2 inches long as shown in Figure 39. To ensure the unidirectionality of heat flow, the temperature distribution inside the copper test specimen was obtained by solving the general equation of conduction at steady state conditions numerically using the finite difference method. Under steady state conditions, the general conduction equation in the cylindrical coordinates is

$$\frac{\partial^2 T}{\partial r^2} + \frac{1}{r} \frac{\partial T}{\partial r} + \frac{\partial^2 T}{\partial z^2} = 0 \quad (A.1)$$

To solve this differential equation subject to the boundary conditions depicted in Figure 39 by the finite difference method, the domain was subdivided into small sections by setting up a system of nodes. According to the finite difference method the following equations apply at any node (i,j).

FIG. 39 THE TEST SPECIMEN AND THE BOUNDARY CONDITIONS

$$\frac{\partial T}{\partial r} = \frac{T_{i+1,j} - T_{i-1,j}}{2\Delta R} \quad (\text{A.2})$$

$$\frac{\partial^2 T}{\partial r^2} = \frac{T_{i+1,j} + T_{i-1,j} - 2T_{i,j}}{\Delta R^2} \quad (\text{A.3})$$

$$\frac{\partial^2 T}{\partial z^2} = \frac{T_{i,j-1} + T_{i,j+1} - 2T_{i,j}}{\Delta z^2} \quad (\text{A.4})$$

For the nodes near the boundary as shown in Figure 40b,

$$\frac{\partial T}{\partial r} = \frac{1}{\Delta R} \left[\frac{1}{\epsilon(1+\epsilon)} T_A - \frac{\epsilon}{1+\epsilon} T_{i-1,j} - \frac{1-\epsilon}{\epsilon} T_{i,j} \right] \quad (\text{A.5})$$

$$\frac{\partial^2 T}{\partial r^2} = \frac{2}{\Delta R^2} \left[\frac{1}{\epsilon(1+\epsilon)} T_A + \frac{1}{1+\epsilon} T_{i-1,j} - \frac{1}{\epsilon} T_{i,j} \right] \quad (\text{A.6})$$

The boundary conditions were described in the form of energy balance at the element concerned. At a node such as in Figure 40c the boundary condition was written in the form

$$\frac{\Delta R}{2} \cdot k \cdot \frac{T_{i,j-1} - T_{i,j}}{\Delta z} + \frac{\Delta R}{2} \cdot k \cdot \frac{T_{i,j+1} - T_{i,j}}{\Delta z} + \Delta z \cdot k \cdot \frac{T_{i-1,j} - T_{i,j}}{\Delta R} = \Delta z \cdot h \cdot (T_{i,j} - T_\infty) \quad (\text{A.7})$$

Application of the finite difference technique transforms the differential equation into a system of linear algebraic equations which are equal to the number of subdivisions. Solving these algebraic equations simultaneously, using the digital computer yielded the temperature at each node. Figure 41 shows the isothermal lines obtained when the following

FIG-40 FINITE DIFFERENCE METHOD

FIG. 41 TEMPERATURE DISTRIBUTION IN A CYLINDRICAL
TEST SPECIMEN

conditions were used:

Heater power q''	= 2,000 BTU/hr. ft ² .
Ambient temperature T_{∞}	= 70°F
Boiling water temperature T_b	= 212°F
Boiling coefficient of heat transfer h_B	= 2000 BTU/hr. ft ² .
Overall coefficient of heat transfer $\bar{h}$	= 0.7 BTU/hr. ft ² .
Radial incremental distance ΔR	= 3/16 inch
Axial incremental distance Δz	= 0.5 inch

The heat flow lines are normal to the constant temperature lines. Examination of the heat flow lines indicated in Figure 41 shows that the heat flux is approximately unidirectional and normal to the boiling surface.

However, the final configuration at the copper test specimen as shown in Figure 4 was not exactly that of a uniform cylinder. To ensure the validity of the procedure used for obtaining the surface temperature by extrapolating the linear correlation of the three temperature measurements at the center line of the specimen, the following analysis was performed.

The unidirectionality of heat was proved for a uniform cross section test specimen by the previous analysis and therefore the heat flow normal to section x-x as indicated in Figure 42 was assumed uniform. This assumption was justified by observation of the linearity of the measured

FIG. 42 BOUNDARY CONDITIONS

temperatures at the center line of the specimen. In accordance with the finite difference technique, the conduction domain considered was subdivided into small sections by setting up a system of 43 nodes. Both the radial incremental distance ΔR and the axial incremental distance Δz were chosen to be 0.05 inch. The boundary conditions shown in Figure 42 were given the following numerical values:

$$\begin{aligned} q'' &= 84726.7 \text{ BTU/hr. ft}^2. \\ h_B &= 2000.0 \text{ BTU/hr. ft}^2. ^\circ\text{F} \\ T_B &= 212.0 ^\circ\text{F} \\ T_\infty &= 70.0 ^\circ\text{F} \\ U &= 50.0 \text{ BTU/hr. ft}^2. ^\circ\text{F} \end{aligned}$$

where the values of q/A , h_B and T_B were based upon the experimental data. The resulting temperature distribution under these boundary conditions is depicted in Figure 43. The extrapolated surface temperature determined experimentally was 232.9°F which represents an average value of the computed temperatures on the different nodes at the surface. The average heat flux at the boiling surface according to the computed temperature distribution is $39980.0 \text{ BTU/hr. ft}^2.$ which is in good agreement with that obtained experimentally under the same condition which was $41,500 \text{ BTU/hr. ft}^2.$ This analysis adds more confidence to the procedure used to calculate both the surface superheat and heat flux.

230.5	230.7	231.0	231.6	232.2	232.8	233.3	233.7	234.0	234.18	234.2
231.1	231.3	231.7	232.3	233.0	233.67	234.2	234.7	234.97	235.1	235.2
231.3	231.7	232.3	233.1	234.0	234.8	235.4	235.86	236.18	236.36	236.4
232.15	232.6	232.8	235.26	236.2	236.8	237.3	237.65	237.84	237.88	

FIG. 43 TEMPERATURE DISTRIBUTION NEAR THE BOILING SURFACE

APPENDIX B INTERFEROMETRY

The principle of interferometry is based upon the interference of reflected light. Recombination of two parts of a monochromatic light beam which has been divided will cause either cancellation or enforcement of light depending upon whether the optical path difference of the two parts is equivalent to half a wave length or equivalent to one wave length respectively.

The modified Michelson interferometer [25] is the interferometer configuration about which the Watson interference objective has been designed. The principle can be understood by viewing Figure 44 in which a monochromatic beam of light may be considered to be focussed on a small hole H situated at the focus of the lens L_1 . The parallel beam leaving this lens strikes a half silvered mirror M_1 inclined at 45 degrees to the axis, part of it being reflected towards M_3 and part of it being transmitted towards M_2 . The two beams are then reflected back by the two surfaces M_2 and M_3 , pass through the lens L_2 and are brought to a focus at E where the eye is placed. By adjustment of the distances $M_1 M_2$ and $M_1 M_3$, the optical lengths of the two paths may be made identically equal and by further fine adjustment in which surface M_2 is tilted, the two images of H formed at E may be made to coincide exactly. When this is the case, a uniform field of illumination

FIG. 44 LIGHT PATH IN A MODIFIED MICHELSON INTERFEROMETER

will be seen at E. If now one of these coincident fronts (say from surface M_3) is distorted by the introduction of something which displaces the beam, dark interference fringes will be seen whenever the path difference of the beam from M_3 is an odd number of half wave lengths behind the corresponding part of the beam from M_2 .

In the case of a conical cavity in the surface being examined, which is M_3 in the schematic sketch, Figure 44, the fringes produced should be in the form of concentric rings corresponding to the different levels of depth in the cavity which created the change in the optical path length of light reflected from the surface.

An example of the shape of the interference fringes around and about the nucleation cavity is shown in Figure 45.

Fig. 45 A Typical Interferogram

APPENDIX C

DETERMINATION OF SURFACE TEMPERATURE UNCERTAINTY

As the surface temperature is obtained indirectly, it is subjected to cumulative inaccuracies due to the uncertainties in thermocouple junction locations. The following analysis is patterned after the corresponding analysis in reference [26].

1. Statistical Study for the Distribution of the Measured Temperatures in a Hole

A typical hole of radius r is shown in Figure 46 with an assumed temperature gradient across the hole. The actual position of the hole center line is $\bar{x}$ and the undisturbed temperature at the center line is $\bar{T}$.

The temperature could be related to position in the hole by the equation,

$$x - \bar{x} = \frac{T - \bar{T}}{\frac{q/A}{K}}$$

(C.1)

The thermocouple reading must lie between the temperatures at $+r$ and $-r$. The quantity $(T - \bar{T})$ is the temperature difference between the measured and the actual reading, i.e., the experimental error.

The limits of $x - \bar{x}$ are

FIG. 46 A TYPICAL HOLE WITH LINEAR TEMPERATURE DROP

FIG. 47 NORMAL DISTRIBUTION OF TEMPERATURE MEASUREMENTS IN A HOLE

$$-r \leq x - \bar{x} \leq +r \quad (C.2)$$

Making Equation (C.2) dimensionless yields

$$-1 \leq \frac{x - \bar{x}}{r} \leq +1 \quad (C.3)$$

In order to specify the distribution of the measured temperature at any hole, a density function representing possible thermocouple locations within the hole is to be chosen. Since the exact distribution of possible locations is unknown, a normal distribution is used. The normal probability density function of x is defined as

$$f(x) = \frac{1}{\sqrt{2\pi} \sigma} \exp \left[-\frac{1}{2} \left(\frac{x - \mu}{\sigma} \right)^2 \right] \quad (C.4)$$

where μ is the mean and σ is the standard deviation.

The distribution of the quantity $\left(\frac{x - \bar{x}}{r} \right)$ will be a normal distribution for the range $-1 \leq \frac{x - \bar{x}}{r} \leq +1$ with mean equal to zero and standard deviation σ

$$f\left(\frac{x - \bar{x}}{r}\right) = \frac{1}{\sqrt{2\pi} \sigma} \exp \left[-\frac{1}{2\sigma^2} \left(\frac{x - \bar{x}}{r} \right)^2 \right] \quad (C.5)$$

where σ is the standard deviation obtained from,

$$\int_{-1}^{+1} f\left(\frac{x - \bar{x}}{r}\right) d\left(\frac{x - \bar{x}}{r}\right) = 0.999 \quad (C.6)$$

From the statistical tables [27], $\sigma = 0.3058$. The distribution

is shown in Figure 47.

From Equation (C.1)

$$\frac{x - \bar{x}}{r} = \frac{T - \bar{T}}{\frac{(q/A)}{K} r} \quad (C.7)$$

Therefore, the quantity $\frac{T - \bar{T}}{\frac{(q/A)}{K} r}$ will have the same distribution as $\left(\frac{x - \bar{x}}{r}\right)$.

2. Distribution of the Error in Wall Temperature

The distribution of temperature measurement errors at the three holes and that resulting around $\bar{T}_w$ are shown in Figure 48.

The experimental errors, both in the holes and at the surface are symmetrical about the actual temperature existing at that location with error mean equal to zero.

Therefore, the distribution of the quantity,

$$\left(\frac{T_w - \bar{T}_w}{\frac{(q/A)}{K} r} \right)$$

is normal distribution with mean equal to zero and standard deviation σ_w . As given by reference [28]

$$\sigma_w = \sqrt{\frac{1}{n} + \frac{\mu'^2}{\sum (\bar{x}_i - \bar{\mu})^2}} \quad (C.8)$$

where; n is the number of thermocouple holes,

$\bar{x}_i$ is the normal distance of the i^{th} hole from the wall, and

$$\mu' = \frac{\sum \bar{x}_i}{n}$$

FIG. 48 SCHEMATIC REPRESENTATION OF DISTRIBUTIONS IN HOLES AND AT SURFACE

The resulting σ_w was equal to 0.35.

Constructing a 90% confidence interval,

$$-1.64 \leq \frac{T_w - \bar{T}_w}{\frac{(q/A)r}{K} \sigma_w} \leq 1.64 \quad (C.9)$$

Taking the value of q/A equal to 120,000 BTU/hr. ft² as the maximum value to be used during the experimentation and r to be chosen as double the actual hole radius to compensate for the uncertainty in the hole location, i.e., $r = 1/16$ inch,

$$-1.638 \leq T_w - \bar{T}_w \leq 1.638 \quad (C.10)$$

Equation (C.10) implies that with 90% confidence the error in the resulting surface temperature will be in the range of ± 1.630 .

It is obvious that as most of the experiments performed were at relatively low heat flux, so this expected error is to be considered the maximum possible error.

APPENDIX D

UNCERTAINTY ANALYSIS

The uncertainty of each computed result was calculated using the following relationship.

$$\frac{W_R}{R} = \left[\left(\frac{\partial R}{\partial V_1} \cdot \frac{W_1}{R} \right)^2 + \left(\frac{\partial R}{\partial V_2} \cdot \frac{W_2}{R} \right)^2 + \dots + \left(\frac{\partial R}{\partial V_n} \cdot \frac{W_n}{R} \right)^2 \right]^{1/2} \quad (D.1)$$

where

R = result computed
 W_R = uncertainty in the result R
 V_n = n^{th} variable
 W_n = uncertainty in the n^{th} variable

Surface Temperature

According to the statistical analysis performed in Appendix C, the error in the extrapolated surface temperature with 90% confidence and at heat flux of 85,000 BTU/hr, ft² is $\pm 1.16^\circ\text{F}$. From Appendix A at the same condition of heat flux, the range of error due to the enlargement of the test specimen cross-sectional area is of the order $\pm 2^\circ\text{F}$. Adding to these values the uncertainty of the potentiometer reading which is about 0.5°F corresponding to an error of 10 microvolts brings the total uncertainty of the surface temperature to 3.66°F under this condition. This corresponds to a determined surface temperature of 232°F so that $W_T/T_W = 1.58\%$.

Heat Flux

The uncertainty of heat flux value due to the uncertainty of the value of the temperature gradient in the copper test specimen is determined by Equation (D.1). Figure 49 represents the temperature data at a certain condition. The slope of the least square fit is $32.24^{\circ}\text{F/inch}$ which corresponds to a heat flux of $85,000 \text{ BTU/hr. ft}^2$. The uncertainty of the measured temperatures according to Appendix C is shown. The steepest possible correlation has a slope of $35.2^{\circ}\text{F/inch}$. The resulting value $W_{q/A}/q/A = 9.37\%$.

X-Y Stage

The uncertainty involved with the two micrometers is ± 0.00005 inches.

Cavity Radius

The uncertainty due to irregularity of the shape of the cavity as viewed in the photographs was 0.005 inches. Taking the magnification factor 120X into consideration makes the uncertainty in the determined cavity radius to be 0.00004 inches.

FIG. 49 THE UNCERTAINTY OF THE TEMPERATURE MEASUREMENTS
AND THE CORRELATED SLOPE

APPENDIX E
EXPERIMENTAL DATA

Table II
SATURATED BOILING OF WATER

Surface (μ in CLA)	Heat Flux q/A (BTU/hr.ft ²)	Superheat ($T_w - T_s$) (°F)	Site Density N/A (sites/in ²)
16	18,388.6	10.2	81.1
	23,213.4	11.5	144.2
	25,857.4	12.0	153.3
	28,313.0	13.3	171.3
	30,544.7	14.8	189.3
	33,017.1	15.2	216.4
	35,901.6	15.7	243.3
	38,219.0	16.2	288.6
	41,619.1	16.4	333.6
	46,409.4	16.7	423.8
	50,478.6	18.2	—
	52,994.0	18.4	504.7
	56,196.1	18.7	—
	64,128.5	18.8	—
	79,272.0	20.5	—
	95,651.5	21.8	—
	108,838.1	22.5	—
	140,619.0	24.5	—
5	31,000.0	15.0	144.3
	35,798.0	16.1	207.4
	38,000.0	16.4	257.0
	41,104.0	16.7	279.4
	46,100.4	17.8	306.5
	50,349.0	18.5	378.7
	63,870.9	20.2	—
	78,808.5	21.7	—
	93,591.0	23.1	—
	109,971.0	23.4	—
	151,023.8	25.3	—

Table II continued

Surface (μ in CLA)	Heat Flux q/A (BTU/hr.ft ²)	Superheat ($T_w - T_s$) (°F)	Site Density N/A (sites/in ²)
4	16,894.9	9.6	—
	18,800.7	12.1	—
	19,476.3	13.1	—
	21,479.2	13.5	—
	24,106.1	15.5	—
	26,475.5	16.9	40.5
	29,308.5	17.2	81.1
	31,265.8	18.1	94.6
	33,789.8	18.7	121.7
	36,159.0	19.0	142.0
	38,889.1	19.8	155.6
	41,516.1	20.6	169.1
	45,636.7	20.9	209.7
	52,178.4	22.1	—
	61,381.7	22.6	—
	77,675.3	24.7	—
	91,634.2	25.7	—
	107,486.0	26.5	—
	134,695.5	28.7	—

Table III

OBSERVED ACTIVE CAVITIES RADII

Surface (μ in CLA)	Heat Flux q/A (BTU/hr.ft ²)	Representative Cavity Radius* $\times 10^4$ (in.)
16	52,994.0	1.192 1.558 1.733 1.808 1.900 2.075 2.450 2.508 2.683 2.808 3.125 3.345 3.383 3.617 3.667 4.440 4.442 5.200
16	38,219	1.492 1.667 1.758 1.817 1.833 2.175 2.575

* These cavities were observed at three different fields of view chosen arbitrarily.

Table III continued

Surface (μ in CLA)	Heat Flux q/A (BTU/hr.ft ²)	Representative Cavity Radius $\times 10^4$ (in.)
16	38,219.0	3.033 3.133 3.692 3.925 4.100 4.316 4.333 4.342 4.433 4.483 5.929
16	28,313	2.325 2.333 2.458 2.692 2.825 2.908 3.200 3.600 3.658 3.700 3.820 4.108 4.770 5.000
5	38,000	1.400 1.416 1.442 1.458 1.517

Table III continued

Surface (μ in CLA)	Heat Flux q/A (BTU/hr.ft ²)	Representative Cavity Radius $\times 10^4$ (in.)
5	38,000	1.700 1.760 1.770 1.810 2.090 2.120 2.133 2.550 2.708 3.350
5	35,798	1.525 1.725 1.808 1.825 1.850 1.940 2.108 2.150 2.200 2.330 2.400 2.410 2.558 2.658 2.683 2.875 3.450 3.567

Table III continued

Surface (μ in CLA)	Heat Flux q/A (BTU/hr.ft ²)	Representative Cavity Radius $\times 10^4$ (in.)
5	35,798	2.410 2.558 2.658 2.683 2.875 3.450 3.567
5	31,000.0	1.590 1.660 1.890 2.083 2.350 2.610 2.700 2.850 2.950 3.330 3.460 3.670 4.420 4.780
4	41,516	1.100 1.300 1.470 1.500 1.570 1.630 1.642 1.670 1.700 1.750

Table III continued

Surface (μ in CLA)	Heat Flux q/A (BTU/hr.ft ²)	Representative Cavity Radius $\times 10^4$ (in.)
4	41,516	1.760 1.830 1.850 2.100 2.150 2.610 3.580
4	36,159	1.317 1.325 1.475 1.500 1.592 1.658 1.660 1.670 1.742 1.760 1.925 1.996 2.033 2.175 2.175 2.400 2.404 2.550 2.750 2.800 3.000

Table III continued

Surface (μ in CLA)	Heat Flux q/A (BTU/hr.ft. ²)	Representative Cavity Radius $\times 10^4$ (in.)
4	29,308	1.508 1.600 1.730 1.747 1.851 2.142 2.263 2.275 2.390 2.490 2.800 2.925 3.250 3.440

APPENDIX F
PROPERTIES OF THE
COPPER SPECIMEN

Supplier:	Noranda Copper
Type:	Electrolytic Copper
Composition:	99.9% Copper, .04% Oxygen
Thermal Conductivity:	220 BTU/hr. ft. °F
Specific Heat:	.092 BTU/lb. °F
Density:	.32 lb./cu. inch

NOMENCLATURE

SYMBOL	DESCRIPTION	UNITS
A	Parameter $A = 2\sigma T_s / \rho_v h_{fg}$	ft. °R
B	Kurihara and Myer's Correlation Constant	μ inch °R
C	Specific Heat	BTU/lb _m °F
c_1	Constant $c_1 = (1 + \cos\theta) / \sin\theta$	-
c_2	Constant $c_2 = 1 / \sin\theta$	-
c_3	Constant $c_3 = (1 + \cos\theta)$	-
C_{sf}	Rohsenow Correlation Constant	-
E	Characteristic term for Kurihara and Myer's Correlation	μ inch
$f(N/A)$	Frequency of occurrence of nucleation site density	-
g	Gravitational Acceleration	ft./hr. ²
g_c	Conversion factor	lb _m ft./hr. ² · lb _f
h	Heat transfer coefficient	BTU/hr. ft. ² °F
h_{fg}	Latent heat of vaporization	BTU/lb _m
J	Mechanical equivalent of heat	lb _f ft./BTU
k	Thermal conductivity	BTU/hr.ft. °F
M	Molecular weight	-
N/A	Total nucleation site density	in. ⁻²
$(N/A)_{r_c}$	Nucleation site density for cavities of radius equal to or greater than r_c	in. ⁻²
n	Cavity size distribution function	-
P	Pressure	lb _f /ft. ²
Pr	Prandtl number	-
q/A	Heat flux	BTU/hr. ft. ²

q''	Heat flux	BTU/hr. ft ² .
R	Universal gas constant	ft. lb _f /mol °R
R	Gas constant	BTU/lb _m °R
r	Nucleus radius	inch
r_c	Cavity radius	inch
T	Temperature	°R
t	Time	hr.
v	Specific volume	ft ³ /lb _m
δ	Extrapolated thermal layer thickness	inch
θ	Temperature difference $\theta = T - T_\infty$	°R
ϕ	Conical angle	
α	Contact angle	
$n(y)$	Number of grooves of depth between y and $(y+1)$ per unit area	ft ⁻²
ρ	Density	lb _m /ft ³
σ	Surface tension	lb _f /ft
μ	Coefficient of viscosity	lb _m /hr. ft.
α	Thermal diffusivity	ft ² /hr
β	Parameter θ/θ_w	
η	Parameter x/δ	

SUBSCRIPTS

l
 v
 w
 s
 o

DESCRIPTION

liquid
 vapour
 surface
 bulk
 saturation
 incipience

REFERENCES

1. Jakob, M., Heat Transfer, Vol. 1, Wiley, New York, pp. 631-642, 1949.
2. Rohsenow, W. M., "A Method of Correlating Heat Transfer Data for Surface Boiling of Liquids", Trans. ASME, 74, p. 969, 1952.
3. Fritz, W., "Physik Zeitschrift", Vol. 36, p. 379, 1935.
4. Corty, C. and Foust, A. S., "Surface Variables in Nucleate Boiling", Chem. Eng. Progress Symp. Series, 51, 17, p. 1, 1955.
5. Clark, H. B., Strenge, P. S. and Westwater, J. W., "Active Site for Nucleate Boiling", Chem. Eng. Progress Symp. Series, 55, p. 103, 1959.
6. Harrison, W. B. and Zelving, L., A.I.Ch.E.-ASME Joint Heat Transfer Conference, Aug. 11-14, State College, Pennsylvania, 1957.
7. Bankhoff, S. G., "Ebullition from Solid Surface in the Absence of Pre-existing Gaseous Phase", Trans. ASME, 79, p. 735, 1957.
8. Bankhoff, S. G. "On the Mechanism of Subcooled Nucleate Boiling", Chem. Eng. Progress Symp. Series, 57, 1961.
9. Kurihara, H. M. and Myers, J. E., "The Effect of Superheat and Surface Roughness on Boiling Coefficients", A.I.Ch.E. Journal, 6, p. 83, 1960.
10. Griffith, P. and Wallis, J. D. "The Role of Surface Conditions in Nucleate Boiling", Chem. Eng. Progress Symp. Series, 56, p. 49, 1960.
11. Westwater, J. W. and Gaertner, R. F., "Population of Active Sites in Nucleate Boiling Heat Transfer", Chem. Eng. Progress Symp. Series, 56, p. 39, 1960.
12. Gaertner, R. F., "Distribution of Active Sites in Nucleate Boiling of Liquids", Chem. Eng. Progress Symp. Series, 59, 1963.
13. Anderson, D., Judd, R. L. and Merte, H., "Site Activation Phenomenon in Saturated Nucleate Boiling", Proceedings ASME Joint Fluids Engineering and Heat Transfer Symposium on the Role of Nucleation in Boiling and Cavitation, Detroit, 1970.

14. Hsu, Y. Y., "On the Size Range of Active Nucleation Cavities on a Heating Surface", Trans. ASME Journal of Heat Transfer, p. 207, 1962.
15. Hall, I. S., and Hatton, A. P., "The Influence of Surface Roughness and a Wetting Additive on Pool Boiling on Horizontal Rods", Proceedings Inst. Mech. Eng., 180, 1965-1966.
16. Hatton, A. P. and Hall, I. S., "Photographic Study of Boiling on Prepared Surfaces", Proceedings of the Third International Heat Transfer Conf. Chicago, 1966.
17. Vachon, R. I., Tanger, G. E., Davis G. E. and Nix, G. H., "Pool Boiling on Polished and Chemically Etched Stainless Steel Surfaces", Trans. ASME, Journal of Heat Transfer, 90, p. 231, 1968.
18. Han, C. and Griffith, P., "The Mechanism of Heat Transfer in Nucleate Pool Boiling", In. Journal of Heat and Mass Transfer, 8, p. 887, 1965.
19. Wiebe, J. R. and Judd, R. L., "Superheat Layer Thickness Measurements in Saturated and Subcooled Nucleate Boiling", Trans. ASME, Journal of Heat Transfer, p. 445, 1971.
20. Bankhoff, S. G., "Entrapment of Gas in the Spreading of Liquid over a Rough Surface", A.I.Ch.E. Journal 4, p. 24, 1958.
21. Rohsenow, W. M., "Nucleation with Boiling Heat Transfer," Proceedings ASME Joint Fluids Engineering and Heat Transfer Division Symposium on the Role of Nucleation in Boiling and Cavitation, Detroit, 1970.
22. De, P. L. and Judd, R. L., "Nucleation in Saturated and Subcooled Boiling", C.J.Ch.E., Vol. 5, p. 767, 1973.
23. Rao, S. N., "Effect of Surface Active Agents in Boiling Heat Transfer", M.Eng. Thesis, McMaster University, 1967.
24. Brown, W. T., "Study of Flow Surface Boiling", Ph.D. Thesis, Mech. Eng. Dept., M.I.T., 1967.
25. Johnson, B. K., Optics and Optical Instruments, Dover Publications Inc., p. 200, 1960.
26. Rohsenow, W. M. and Wilcox, S. J., "Film Condensation of Potassium using Copper Condensing Block for Precise Wall Temperature Measurements, Trans. ASME, Journal of Heat Transfer, p. 359, 1970.
27. Handbook of Tables of Probability and Statistics, The Chemical Rubber Company, 1968.

28. Hald, A., Statistical Theory with Engineering Applications, Wiley, New York, p. 536, 1952.